



**ZINC OXIDE
GRADE 205XL**

Description & Uses

Grade 205L is a large particle size French Process, statistically controlled zinc oxide. 205XL is used by the ceramics, electronics, paint and coating industries and in those applications which derive benefits from larger than normal particles.

Typical Technical Values*

Chemical Analysis (%)	Range	Nominal	Method
ZnO (Zinc Oxide) dry basis	≥99.5	99.7	USZ
Pb (Lead)	≤.05	.01	D4075
Cd (Cadmium)	≤.01	.002	D4075
Cu (Copper)	≤.006	nil	D4075
Fe (Iron)	≤.006	nil	D4075

Physical Properties

Surface Area (m ² /g)	2.5-3.5	2.7	D4315
Fineness passing 325 mesh (%)	≥99.9	99.98	D4315
Heat Loss/Moisture (%)	<.2	.1	D280
Specific Gravity	N/A	5.6	USZ
Apparent Density (Powder)	20-40	30	USZ
Oil Absorption (lbs. oil/100 lbs. pigment)	15-30	22	USZ

Standard packaging in 50 pound net weight bags on 48X40 wood pallets. 2,500 pounds net weight.

**U.S. Zinc can produce Zinc Oxide to meet individual customer specifications superseding the above. Please contact customer service for additional information.*

Revised 03-17-04

U. S. ZINC, a Votorantim Metais company
6020 Navigation Blvd., Houston TX 77011 USA. Phone (001) 713-926-1705, Fax (001) 713-924-4828
Ed.Smith@USZinc.com www2.USZinc.com, www.VMetais.com.br